



Rig 764 Inventory

(Nomac Rig 134)

DRAWWORKS:

National 80-UE 1000 HP
Powered by (2) GE 752 motors

AUXILIARY BRAKE:

Baylor 6032

MAST:

Drilling Structures, Inc. 142'
750,000 lbs SHL 12 lines

SUBSTRUCTURE:

Drilling Structures, Inc. Box-on-Box
2-box w/ 22' floor height

TRAVELING EQUIPMENT:

BLOCK HOOK:
National Oilwell 545G350, 350 ton

ROTARY TABLE:

Mud King RT-275

DRIVE SYSTEM:

Ross Hill 3 x 4 SCR Model 1400

ENGINE/GENERATORS:

2 - Caterpillar 3512B / Kato 1365kW
generators
1 - Caterpillar 3512B / Caterpillar 1365kW
generators

MUD PUMPS:

2 - Emsco FB1600 type, 1600 HP
Each powered by (2) 1130 HP motors

MUD SYSTEM:

2 tank, 1050 Bbl w/ 100 Bbl pre-mix

SOLIDS CONTROL EQUIPMENT:

SHAKERS:
2 - Mi Swaco Mongoose - PT

DEGASSER:

Derrick Vacuflo 500

DESANDER:

Derrick DSV-10-2

DESILTER:

Derrick S-412-S

BOP EQUIPMENT:

ANNULAR:
Shaffer Style Spherical 11" – 5K WP

DOUBLE:

Cameron Type U 11" – 10K WP

SINGLE:

Cameron Type U 11" – 10K WP

CHOKE MANIFOLD:

4" x 3" 5000 PSI

CLOSING UNIT:

Advanced Pressure 6 station, 200 gallon

AUXILIARY EQUIPMENT:

Iron Roughneck:
Varco ST-80C

Water Tank:
500 Bbl

Fuel Tank:
12,000 gallons

Trip Tank:
100 Bbl

Air Hoist:
2 - Ingersoll Rand K5UL

Pipe Spinner:
Oil Works 35C-7

Wireline Machine:
Five Star

EDR:
MD Totco

TOP DRIVE:

NOV TDS-11, 500 ton

MULTI-WELL PAD SITE:

Beam Rail Skidding System
Capabilities: 120'

TUBULARS:

Drill Pipe: 18,000' 5"
Drill Collars: As Required